

EASTFINE

Specification

For LED Strip



RoHS



Guangdong Yu chen Optoelectronic Technology Co., Ltd

Add: Yutong Industrial Park, Liyuan Road, Zhangmutou town, Dongguan City, Guangdong Province.

Tel: 0769-82933110 Fax: 0769-82933110

E-mail: eastfine@eastfineled.com


www.eastfineled.com

■ Table of Contents

1. Product Naming Convention	03
2. Product Information	03
2.1.Introduction	
2.2.Product Features	
2.3.Areas of application	
3. Specifications&Parameters	04
3.1 Measurement (Unit:mm)	
3.2 Electrical Data	
3.3 Spectrum Data	
4. Connection Methods	05
5. Packaging	06
6. Appendix	06
6.1.(X,Y) Chromaticity Diagram	

1.Product Naming Convention

XX-X-XX-XXX-X



Working voltage: 5V (A) , 12V (B) , 24V (C) , 36V (D) , 48V (H)

LED Quantity/Meter: 70LED (070) 、 120LED (120) 140 (140)

Color/CCT: White (00-99) , WW-CW (TW) , RGB (RG) RGBW (RW) , Red (RE) , Green (GR) , Blue (BL), Yellow (YE) , Pink (PI) , Orange (OR) , Violet (UV)

LED Type: 2110 (A) , 2216 (B) , 2835 (C) , 3014(D) 3030 (E) , 3535 (G), 5050 (H)

LED Strip: Bare plate (SA) , Surface glue (SB) , Silicone tube (SC) , Heat shrinkable casing (SD) , Half sleeve drops of glue (SE) , All glue (SF)

For Example: SA-C30120C

LED Strip Bare plate 2835 3000K 120LEDS/m DC24V

2.Product Information

2.1.Introduction

LED Strip with wide beam angle and high output lumen.

So, it is wonderfully suitable for uniform linear lighting of every room.

Even for those who want to let their creativity run wild with strips, our LED Strip is suitable as well. High color rendering and high flexibility give you a plenty of scope and bring art to your wall with light. Simply bend the LED Strip into the desired shape and attach it to your wall with accessories.

2.2.Product Features

- (1).High quality and high brightness SMD LED chip.
- (2).Variety of monochromatic lights for option including Red, Green, Blue, Yellow, Pink, Orange, Violet and whitelight.
- (3).Flat profile, good choice for recessed mounting.
- (4).Environmentally friendly & energy efficient.
- (5).High color consistency.
- (6).Perfect softness, gentle emitting, Not dazzling.
- (7).3-5 years warranty.

2.3.Areas of application

- (1). Indoor Contour/Border Lighting.
- (2). Architectural Outline/Decorative Lighting.
- (3). Cove/Accent Lighting.
- (4). Facade/Floor Lighting.
- (5). Signage/Guide Lighting.



Flame
Resistant



Saltwater
Resistant



Solvents
Resistant



UV
Resistant



IK06
Protection



>3
YEAR
Warranty




-40°C
+50°C
Operating
Temperature



-40°C
+60°C
Storage
Temperature

3. Specifications&Parameters

3.1 Measurement (Unit:mm)




3.2 Electrical Data

Model No.	Voltage	Current	Power (W/M)	IP	Unit Length (mm)	FPC Width (mm)	Strip Width (mm)	Height (mm)
SA-C27192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-C30192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-C40192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-C50192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-C65192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-CRE192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-CGR192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-CBL192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-CYE192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-CPI192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-CUV192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9
SA-COR192C	DC24V	0.67A	16.0	IP20	31.25	10	10	0.9

3.3 Spectrum Data

Model No.	CCT	Lumens (lm/M)	CRI	LED Type	LEDs/M	Beam Angle	Standard Packing	Weight (g/5M)
SA-C27192C	2700K	1450	90	2835	192	120°	5M/Roll	145
SA-C30192C	3000K	1480	90	2835	192	120°	5M/Roll	145
SA-C40192C	4000K	1500	90	2835	192	120°	5M/Roll	145
SA-C50192C	5000K	1530	90	2835	192	120°	5M/Roll	145
SA-C65192C	6500K	1570	90	2835	192	120°	5M/Roll	145
SA-CRE192C	Red	320	—	2835	192	120°	5M/Roll	145
SA-CGR192C	Green	533	—	2835	192	120°	5M/Roll	145
SA-CBL192C	Blue	266	—	2835	192	120°	5M/Roll	145
SA-CYE192C	Yellow	482	—	2835	192	120°	5M/Roll	145
SA-CPI192C	Pink	397	—	2835	192	120°	5M/Roll	145
SA-CUV192C	Purple	12.2	—	2835	192	120°	5M/Roll	145
SA-COR192C	Orange	1200	—	2835	192	120°	5M/Roll	145

4. Connection Methods



5. Packaging



6. Appendix

6.1 (X,Y) Chromaticity Diagram

